



FDQR.MH61555 Rainwater Catchment System Components

[Page Bottom](#)

Rainwater Catchment System Components

[See General Information for Rainwater Catchment System Components](#)**MOMENTIVE PERFORMANCE MATERIALS**

MH61555

260 HUDSON RIVER RD
WATERFORD, NY 12188-1910 USA

NSF Protocol P151**RAINWATER CATCHMENT SYSTEM COMPONENTS**

Trade Dsg/Product	Water Contact Mtl	Size Range
Enduris 3502, White (1)	Coating	N/A
Enduris 3504, Medium Grey (1)	Coating	N/A
Enduris 3505, Tan (1)	Coating	N/A
Enduris 3508, Dark Grey (1)	Coating	N/A

(1) Manufacturer's instructions for application must be followed.

- Order of application: Spray = 1 coat. Roller = 2 to 3 coats.
- Primer: None
- Thinning: None
- Application Method: Spray, brush, or roller
- Application Thickness: 36 mils dry
- Final Cure Time: Temperature and Moisture Dependent. 32F - cure time 24 hours. 70F - cure time 4 to 6 hours.

[Last Updated](#) on 2016-11-30[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".