

PG-1395 SILICONE GEL



PROGUARD SILICONE 1395 SERIES BUTTER GRADE SILICONE GEL FOR PROFESSIONAL USE ONLY

PRODUCT INFORMATION

BASIC USES: ProGuard 1395 Series Butter Grade Silicone Gel is an exceptionally versatile, tough, yet flexible membrane that is easily brush or trowel-applied at thicknesses up to 1/4". It is also an excellent adhesive and suitable for direct-to-metal (DTM) repairs, spray polyurethane foam, smooth built up, smooth modified, granulated modified, aged EPDM, flashings, fasteners and drains.

COMPOSITION AND MATERIALS: ProGuard 1395 Series Butter Grade Silicone Gel is a dispersion of silicone rubber. This sealant is a one-part, ready-to-use material that can be applied easily to a dry, frost-free surface, and cures at normal temperature by reacting with moisture in the air.

SIZES: ProGuard 1395 Series Butter Grade Silicone Gel is available in 1- and 2-gallon containers.

STORAGE AND SHELF LIFE: ProGuard 1395 Series Butter Grade Silicone Gel has a shelf life of 36 months (3 years) from date of manufacture. Refer to product packaging.

SPREAD RATE (RANGE):
1/16" = 22-25 sq/ft., 1/8" = 10-12 sq/ft.

COLORS:

- White
- Light Gray

PHYSICAL PROPERTIES

These values are not intended for use in preparing specifications.

AS SUPPLIED

Solids Content	95 (-/-3)	percent by volume ASTM D-2697-3
Tack-Free Time	1-2 hrs.	
Cure Time	12-18 hrs.	

AS CURED

Tensile Strength	130	die C psi ASTM D-412
Elongation	275	percent ASTM D-412
VOC Content	<50g/l	grams/liter



ORDERING INFORMATION:

Available in 1-gallon pails (3.78 liters), and in 2-gallon pails (7.57)

SHIPPING INFORMATION:

CONTAINER	SIZE	CLASS
1 gal.		
2 Gal.		

D.O.T. Classification: Roof Coating, Not Regulated, NFM #170080

HMIS® RATING:

Health 2, Flammability 1, Reactivity 0, Protection X
0=Minimal 1=Slight 2=Moderate 3=Serious
4=Severe