



## GE UltraSpan\* UST Silicone Sheet

### Product Description

Translucent silicone rubber sheet or 'boot' material for use in curtainwall splice and transition applications.

#### 12" wide rolls

**GE part#:** UST2201.120

**SAP#:** 96339

**Length x width:** 100 ft. roll x 12" wide

**Thickness:** 0.022"

**Shipping Weight:** 14.3 Lbs. (6.49 Kg.)

#### 6" wide rolls

**GE part#:** UST2201.060

**SAP#:** 96336

**Length x width:** 100 ft. roll x 6" wide

**Thickness:** 0.022"

**Shipping Weight:** 7.15 Lbs. (3.25 Kg.)



6" and 12" wide rolls shown

Other widths available: 2" to 36" on Made To Order basis (6" & 12" are Made To Stock)

### Typical Properties:

Tensile Strength (ASTM D412): 1103 psi (7.6 MPa)

Ultimate Elongation (ASTM D412): 555%

Hardness (Type A indenter): 35

Silicone Durability - UltraSpan cured silicone rubber exhibits excellent long term resistance to natural weathering including: extreme temperatures, ultraviolet radiation, rain and snow, with negligible change in elasticity.



Easily scissor cut



Curtainwall splice



Licensed  
Products

GE is a registered trademark of General Electric Company and is under license by Momentive Performance Materials Inc.  
\*UltraSpan is a trademark of Momentive Performance Materials Inc.