

Enduris™ Roof Coating Warranties

Effective February 13, 2023

Minimum Dry Film Thickness and Application Rates

| Warranty Type | 10 Year | 15 Year | 20 Year | 30 Year |
|---------------------------------|-----------------------|-----------------------|-----------------------|----------------|
| Product | 21 DFT ⁽¹⁾ | 28 DFT ⁽¹⁾ | 36 DFT ⁽¹⁾ | |
| (for all Applicators) | 24-25 wet mils | 32-34 wet mils | 40-43 wet mils | Not Available |
| Product Plus | 21 DFT | | 28 DFT | 36 DFT |
| (for Authorized Applicators) | 24-25 wet mils | Not Available | 32-34 wet mils | 40-43 wet mils |
| Labor & Material | 21 DFT | 28 DFT | 36 DFT | |
| (for Authorized Applicators) | 24-25 wet mils | 32-34 wet mils | 40-43 wet mils | Not Available |
| Application Rates | | | | |
| Theoretical ⁽¹⁾ | 1.5 gallons/SQ | 2.0 gallons/SQ | 2.5 gallons/SQ | |
| Practical ⁽²⁾ | 1.8 - 2.0 gallons/SQ | 2.5 gallons/SQ | 3.0 gallons/SQ | |
| Recoat Applications | | | | |
| New Coating DFT | 15 mils | 20 mils | Not Available | Not Available |
| Total DFT | 30 mils minimum | 35 mils minimum | | |

⁽¹⁾ Theoretical Application Rates to achieve minimum DFT.

⁽²⁾ Practical Rates are higher to allow for surface texture and porosity, wind loss and material left in container, on rollers and/or spray equipment lines. Each roof and project is different and the practical rate increase will vary.



Silicones

Fees

| Warranty Type | 10 Year | 15 Year | 20 Year | 30 Year |
|------------------|------------------------------------|------------------------------------|------------------------------------|---------------|
| Product | No Fee | No Fee | No Fee | Not Available |
| Product Plus | No Fee | Not Available | No Fee | No Fee |
| Labor & Material | \$1,800* plus \$.04/square foot | \$1,800* plus \$.08/square foot | \$1,800* plus \$.12/square foot | Not Available |

Note: System warranties for Solar projects may be available for an additional cost. Contact Momentive for more information.

Approved Products and Basecoat Requirements (Always test adhesion)

| Substrate (3)(4) | Basecoat or cleaner | | |
|--|--|--|--|
| Asphaltic surfaces such as BUR or ModBit | Optional: Asphalt Bleed Blocker to prevent bleed through into light color coating. Apply at 1 gallon/100 sq. ft. (2 gal for new asphalt) | | |
| Aged EPDM | Commercial biodegradable cleaners (Simple Green or similar) | | |
| Aged TPO, PVC, Hypalon® | Commercial biodegradable cleaners (Simple Green or similar) | | |
| Metal | None | | |
| SPF | 2 color systems required over new SPF with min. 15 mil dark basecoat | | |
| Structural Concrete | None | | |

- (3) Warranties are for GE Silicones coatings and do not include the substrate to which the coating is applied or for basecoats that are not GE Silicones products.
- (4) Do not apply to:
 - a. Aluminized coatings
 - b. Ballasted single-ply membranes
 - c. Coal tar

R. 2023-01-03

^{*}Additional fees may apply for multiple buildings or multiple roof areas at different elevations.