

Revision Date: 02/24/2020

RAIN-STOP

SAFETY DATA SHEET

1. Identification

Product identifier: RAIN-STOP

Other means of identification

Synonyms: Mastic Coating

Recommended use and restriction on use

Recommended use: Protection of construction materials

Restrictions on use: For industrial use only.

Manufacturer/Importer/Distr :

ibutor Information

Proguard Building 1001 B Ave., Ste. 100

Coronado, CA 92118

Contact person : sales@proguardbuilding.com

Telephone : General information

+1-844-766-4273

Emergency telephone

number

Supplier : CHEMTREC

1-800-424-9300

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 4

Health Hazards

Carcinogenicity Category 1A
Toxic to reproduction Category 2

Unknown toxicity - Health

Acute toxicity, oral	0 %
Acute toxicity, dermal	0 %
Acute toxicity, inhalation, vapor	0 %
Acute toxicity, inhalation, dust or mist	0 %

Label Elements

Hazard Symbol:

SDS_US 1/16



Revision Date: 02/24/2020

RAIN-STOP



Signal Word: Danger

Hazard Statement: H227; Combustible liquid.

H350; May cause cancer.

H361; Suspected of damaging fertility or the unborn child.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use

personal protective equipment as required.

Response: IF exposed or concerned: Get medical advice/attention. In case of fire: Use

alcohol resistant foam for extinction.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and

vapor. May cause flash fire or explosion.

Substance(s) formed under the

conditions of use:

Generates methanol during cure.

3. Composition/information on ingredients

SDS_US 2/16



Revision Date: 02/24/2020

RAIN-STOP

Mixtures

Chemical Identity	CAS number	Content in percent (%)*	Notes
(1) Calcium Carbonate	471-34-1	20 - <50%	# This substance has workplace exposure limit(s).
(1) TITANIUM DIOXIDE	13463-67-7	1 - <5%	# This substance has workplace exposure limit(s).
Octadecanoic acid	57-11-4	1 - <5%	# This substance has workplace exposure limit(s).
Titanium, Bis(ethyl acetoacetato)-diispropoxy	27858-32-8	1 - <5%	No data available.
Titanium, (ethyl 3- oxobutanoato-O1',O3)(2,4- pentanedionato-O,O')[1,3- propanediolato(2-)-O,O']-	82089-64-3	0.1 - <1%	No data available.
(1) QUARTZ	14808-60-7	0.1 - <1%	# This substance has workplace exposure limit(s).
Octamethylcyclotetrasiloxane	556-67-2	0.1 - <1%	# This substance has workplace exposure limit(s).

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

General information: No action shall be taken involving any personal risk or without suitable

training.

Ingestion: If swallowed, do NOT induce vomiting. Give a glass of water.

Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration

using a barrier device. If breathing is difficult give oxygen. Get medical

attention.

Skin Contact: Wash contaminated clothing before reuse. In case of contact, immediately

flush skin with plenty of soap and water for at least 15 minutes. Get medical

attention.

Eye contact: In case of contact with eyes, rinse immediately with plenty of water and

seek medical advice.

SDS_US 3/16



Revision Date: 02/24/2020

RAIN-STOP

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Treatment is symptomatic and supportive.

5. Fire-fighting measures

General Fire Hazards: Fire residues and contaminated fire extinguishing water must be disposed

of in accordance with local regulations. Use standard firefighting procedures and consider the hazards of other involved materials.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Water spray Carbon dioxide Foam.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

In case of fire, carbon monoxide and carbon dioxide may be formed. Acute overexposure to the products of combustion may result in irritation of the respiratory tract. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

When using do not smoke. Do not empty into drains.

Special protective equipment

for fire-fighters:

Combustible This product or a component thereof can flow along surfacesto reach a distant ignition source and flash back. Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing

apparatus with full face mask and full protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Product releases methanol during application and curing. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Avoid inhalation of vapors and spray mists. Keep container closed. Keep out of reach of children. See Section 8 of the SDS for Personal Protective

Equipment.

SDS_US 4/16



Revision Date: 02/24/2020

RAIN-STOP

Methods and material for containment and cleaning

up:

Wear proper protective equipment as specified in the protective equipment section. Wipe, scrape, or soak up in an inert material and put in a container intended for flammable materials for disposal. Warn other workers of spill.

Keep unauthorized personnel away.

Notification Procedures: Caution: Contaminated surfaces may be slippery. See Section 8 of the SDS

for Personal Protective Equipment.

Environmental Precautions: Do not allow runoff to sewer, waterway or ground.

7. Handling and storage

Precautions for safe handling: Sensitivity to static discharge is expected; material has a flash point below

200 F. Do not get in eyes, on skin, on clothing. Do not taste or swallow. Use only in well-ventilated areas. See Section 8 of the SDS for Personal

Protective Equipment.

Conditions for safe storage, including any incompatibilities:

Keep container tightly closed. Recommended storage in original container

below 30'C (85'F).

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source		
(1) Calcium Carbonate - Total	REL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)		
(1) Calcium Carbonate - Respirable.	REL	5 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)			
(1) Calcium Carbonate - Total dust.	PEL	15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), amended (02 2006)			
(1) Calcium Carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)		
(1) Calcium Carbonate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)		
(1) Calcium Carbonate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)		
(1) Calcium Carbonate - Total dust.	TWA	15 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)		
(1) Calcium Carbonate - Respirable fraction.	TWA	5 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)		
(1) TITANIUM DIOXIDE	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2015)		
(1) TITANIUM DIOXIDE - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)		
	TWA	10 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)		
	TWA	10 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)		
(1) TITANIUM DIOXIDE - Particulate.	ST ESL	50 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)		

SDS_US 5/16



Revision Date: 02/24/2020

RAIN-STOP

	AN ESL	5 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
(1) TITANIUM DIOXIDE - Total dust.	TWA PEL	10 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
(1) TITANIUM DIOXIDE - Respirable fraction.	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
(1) TITANIUM DIOXIDE - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
(1) TITANIUM DIOXIDE - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
(1) TITANIUM DIOXIDE - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
(1) TITANIUM DIOXIDE	IDLH	5,000 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
Octadecanoic acid - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2017)
Octadecanoic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2017)
Octadecanoic acid - Vapor.	ST ESL	1,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
	AN ESL	100 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
(1) QUARTZ - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2015)
(1) QUARTZ - Respirable dust.	REL	0.05 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
(1) QUARTZ - Respirable dust.	TWA	0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
	OSHA_AC T	0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
(1) QUARTZ - Respirable dust.	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
	TWA	0.1 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	0.1 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
(1) QUARTZ - Particulate.	ST ESL	14 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
	AN ESL	0.27 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
(1) QUARTZ - Respirable dust.	TWA PEL	0.05 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (10 2016)
(1) QUARTZ - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)

SDS_US 6/16



Revision Date: 02/24/2020

RAIN-STOP

(1) QUARTZ	IDLH		50 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
Octamethylcyclotetrasiloxane	TWA	5 ppm		
Octamethylcyclotetrasiloxane - Vapor.	ST ESL	1,0	000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
	AN ESL	1	100 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
Octamethylcyclotetrasiloxane	TWA	10 ppm		US. OARS. WEELs Workplace Environmental Exposure Level Guide, as amended (2014)

Appropriate Engineering

Controls

Eye wash facilities and emergency shower must be available when

handling this product.

Individual protection measures, such as personal protective equipment

General information: Ventilation and other forms of engineering controls are preferred for

controlling exposures. Respiratory protection may be needed for non-

routine or emergency situations.

Eye/face protection: Monogoggles

Skin Protection

Hand Protection: Use chemical-resistant, impervious gloves.

Other: Wear rubber apron. Wear suitable protective clothing and eye/face

protection.

Respiratory Protection: If exposure limits are exceeded or respiratory irritation is experienced,

NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA

regulations (see 29CFR 1910.134).

Hygiene measures: Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing to remove contaminants. Discard contaminated

footwear that cannot be cleaned.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: White
Odor: Alcohol

Odor threshold:

pH:

No data available.

Not applicable

Melting point/freezing point:

Not applicable

SDS_US 7/16



Revision Date: 02/24/2020

RAIN-STOP

Initial boiling point and boiling range: No data available.

Flash Point: 70 °C

Evaporation rate:No data available. **Flammability (solid, gas):**No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

Vapor pressure: No data available.

Vapor density:No data available.Density:No data available.

Relative density: 1.3

Solubility(ies)

Solubility in water:

Solubility (other):

No data available.

No data available.

No data available.

No data available.

Pow:

Auto-ignition temperature:No data available.Decomposition temperature:No data available.SADT:No data available.Viscosity, dynamic:No data available.Viscosity, kinematic:No data available.

VOC: 24 g/l ;

10. Stability and reactivity

Reactivity: No dangerous reaction if used as recommended.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

Hazardous polymerization does not occur.

Conditions to avoid: Keep away from heat. Keep away from sources of ignition - No smoking.

Incompatible Materials: None known.

Hazardous Decomposition

Products:

Carbon oxides Oxides of silicon. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of

formaldehyde are formed due to oxidative degradation.

SDS_US 8/16



Revision Date: 02/24/2020

RAIN-STOP

11. Toxicological information

Information on likely routes of exposure

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

(1) TITANIUM DIOXIDE LD 50 (Rat): > 10,000 mg/kg

Octadecanoic acid LD 50 (Rat, No data available.): > 2,000 mg/kg

Octamethylcyclotetrasilox

ane

LD 50 (Rat): > 4,800 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

(1) TITANIUM DIOXIDE LD 50 (Rabbit): > 10,000 mg/kg

Octamethylcyclotetrasilox LD 50 (Rat): > 2,375 mg/kg

ane

Inhalation

Product: Not classified for acute toxicity based on available data.

SDS_US 9/16



Revision Date: 02/24/2020

RAIN-STOP

Specified substance(s):

(1) TITANIUM DIOXIDE LC50 (Rat): > 6.8 mg/l

Octamethylcyclotetrasilox

ane

LC50 (Rat): 36 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified US. National Toxicology Program (NTP) Report on Carcinogens:

(1) QUARTZ Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

Specified substance(s):

Octamethylcyclotetrasilox

ane

Ames-Test (OECD-Guideline 471 (Genetic Toxicology: Salmonella typhimurium, Reverse Mutation Assay)): negative (not mutagenic)

Mouse Lymphoma Assay (OECD Guidline 476): negative (not mutagenic)

In vivo

Product: No data available.

Specified substance(s):

Octamethylcyclotetrasilox Chromosomal aberration (OECD-Guideline 474 (Genetic Toxicology:

ane Micronucleus Test)) Inhalation (Rat, male and female): negative

Reproductive toxicity

Product: No data available.

SDS_US 10/16



Revision Date: 02/24/2020

RAIN-STOP

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

(1) TITANIUM DIOXIDE LC0 (Leuciscus idus, 48 h): > 1,000 mg/l

Octadecanoic acid LC0 (Brachydanio rerio, 96 h): > 100 mg/l

LC0 (Leuciscus idus, 96 h): > 100 mg/l

Aquatic Invertebrates

Product: No data available.

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Octadecanoic acid LC0 (Brachydanio rerio, 4 d): > 100 mg/l

LC0 (Leuciscus idus, 4 d): > 100 mg/l

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

SDS_US 11/16



Revision Date: 02/24/2020

RAIN-STOP

Product: No data available.

Specified substance(s):

(1) TITANIUM DIOXIDE 0 %

Octamethylcyclotetrasilox

lotetrasilox

3.7 % (29 d, 310 Ready Biodegradability - CO₂ in Sealed Vessels

(Headspace Test)) Not readily biodegradable.

BOD/COD Ratio

ane

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Octamethylcyclotetrasilox

Fathead Minnow, Bioconcentration Factor (BCF): 12.40

ane

Partition Coefficient n-octanol / water (log Kow)
Product:
No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

(1) Calcium Carbonate
 (1) TITANIUM DIOXIDE
 Octadecanoic acid
 Titanium, Bis(ethyl
 No data available.
 No data available.
 No data available.

acetoacetato)-diispropoxy

Titanium, (ethyl 3-

No data available.

oxobutanoato-O1',O3)(2,4-pentanedionato-O,O')[1,3-propanediolato(2-)-O,O']-

(1) QUARTZ
Octamethylcyclotetrasiloxa

No data available. No data available.

ne

Other adverse effects: No data available.

13. Disposal considerations

General information: The generation of waste should be avoided or minimized wherever

possible. Do not discharge into drains, water courses or onto the ground.

See Section 8 for information on appropriate personal protective

equipment.

Disposal instructions: Disposal should be made in accordance with federal, state and local

regulations.

SDS_US 12/16



Revision Date: 02/24/2020

RAIN-STOP

Contaminated Packaging: Dispose of as unused product.

14. Transport information

DOT

UN Number: NA 1993

UN Proper Shipping Name: Combustible liquid, n.o.s.(Decamethylcyclopentasiloxane,

METHYLTRIMETHOXYSILANE, Titanium, Bis(ethyl

acetoacetato)-diispropoxy)

Transport Hazard Class(es)

Class: CBL
Label(s): NONE
Packing Group: III
Marine Pollutant: No

IMDG

Not regulated.

IATA

Not regulated.

Special precautions for user: This product is Combustible as defined by the US Department of

Transportation (DOT). It is regulated for transport in the US in container > 119 gallons. The product is not regulated for transport

by the IATA, ADR/RID, ADNR or the IMDG regulations.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Flammable (gases, aerosols, liquids, or solids)
Carcinogenicity
Reproductive toxicity
Hazards Not Otherwise Classified (HNOC)

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SDS_US 13/16



Revision Date: 02/24/2020

RAIN-STOP

SARA 304 Emergency Release Notification

None present or none present in regulated quantities.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u> <u>Threshold Planning Quantity</u>

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING: This product can expose you to chemicals including (1) TITANIUM DIOXIDE, (1) QUARTZ, which is [are] known to the State of California to cause cancer.

This product can expose you to chemicals including Methanol, which is [are] known to the State of California to cause birth defects or other reproductive harm.

For more information go to www.P65Warnings.ca.gov.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Siloxanes and Silicones, di-Me hydroxy terminated

(1) Calcium Carbonate

Decamethylcyclopentasiloxane

(1) TITANIUM DIOXIDE

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl) -, reaction products with ammonia, octamethylcyclotetrasiloxane and silica

(1) QUARTZ

Octamethylcyclotetrasiloxane

US. Massachusetts RTK - Substance List

Chemical Identity

- (1) Calcium Carbonate
- (1) TITANIUM DIOXIDE
- (1) QUARTZ

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

- (1) Calcium Carbonate
- (1) TITANIUM DIOXIDE

SDS_US 14/16



Revision Date: 02/24/2020

RAIN-STOP

US. Rhode Island RTK <u>Chemical Identity</u>

- (1) Calcium Carbonate
- (1) TITANIUM DIOXIDE

Inventory Status:

iventory Status:		
Australia AICS:	On or in compliance with the inventory	Remarks: None.
Canada DSL Inventory List:	Q (quantity restricted)	Remarks: At least one component is not listed in DSL but all such components are listed in NDSL.
EINECS, ELINCS or NLP:	On or in compliance with the inventory	Remarks: None.
Japan (ENCS) List:	Not in compliance with the inventory.	Remarks: None.
China Inv. Existing Chemical Substances:	On or in compliance with the inventory	Remarks: None.
Korea Existing Chemicals Inv. (KECI):	On or in compliance with the inventory	Remarks: None.
Canada NDSL Inventory:	Not in compliance with the inventory.	Remarks: None.
Philippines PICCS:	Not in compliance with the inventory.	Remarks: None.
US TSCA Inventory:	On or in compliance with the inventory	Remarks: None.
New Zealand Inventory of Chemicals:	Not in compliance with the inventory.	Remarks: None.
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory	Remarks: None.

16.Other information, including date of preparation or last revision

HMIS Hazard ID

Health	*	0	
Flammability		2	
Physical Hazards	1		
PERSONAL PROTECTIO	N		

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

Issue Date: 02/24/2020

Revision Date: No data available.

Version #: 1.2

SDS_US 15/16



Revision Date: 02/24/2020

RAIN-STOP

Further Information: No data available.

Disclaimer:

Notice to reader

Unless otherwise specified in section 1, Proguard products are intended for use in the manufacture and/or formulation of products and are not intended for direct consumer use. These products are not intended for long-lasting (> 30 days) implantation, injection or direct ingestion into the human body, nor for use in the manufacture of multiple use contraceptives. Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SDS_US 16/16