1200 EPDM WASH

Neutral pH EPDM Cleaner/Surfacer

PROFESSIONAL ROOFING SOLUTIONS

For Professional Use Only

OVERVIEW

Using recent breakthroughs in biodegradable and renewable technologies EPDM Wash exceeds the cleaning performance of the traditional, more harmful, EPDM preparation technologies without the flammability or VOC.

DESCRIPTION

- Highest performance EPDM primer/cleaner
- Significantly exceed performance of current EPDM rinseable primer technologies.
- Unique high performance but environmentally friendly cleaner
- Non Flammable
- Non Corrosive, Neutral pH
- All surfactants on <u>www.cleaningrediants.org</u>. These Ingredients have been verified by independent thirdparty experts to pass the Safer Choice Standard, designed to safeguard human and environmental health.
- 100% Biodegradeable formulation
- Meets all US VOC regulations including the most stringent Southern California regulations.
- Significant renewable content.
- Low foaming formulation.
- Does not contain Ammonia, DEA, MEA, Glycol Ethers, Alkylphenol Ethoxylates (APEs), or Phthalates.

RECOMMENDED USES

• Provides maximum adhesion of coating and polyurethane foam to aged EPDM surfaces.

PACKAGING/SHIPPING INFORMATION

| CONTAINER SIZE | SHIPPING CLASS |
|-----------------------------|----------------|
| 5 Gallon pail (18.9 liters) | Class 55 |
| 1 Gallons | Class 55 |

| Property | Test Method | Result |
|---------------------|------------------|---------------|
| Density | ASTM D 1475 | 8.3 lbs gal |
| voc | ASTM D Method 24 | 0 g/ltr |
| рН | ASTM D5464 - 11 | 6.8 to 7.8 |
| Flash Point | ASTM D 1310 | >212°F |
| Temperature Limit | | 0° F to 185°F |
| Shelf Life-Unopened | | 12 months |

Spray onto surface with a low-pressure sprayer such as a garden sprayer at a rate of 1 gal per 400 ft. Leaving on surface at least 10 minutes. Power wash all surfaces with a minimum of 2000 psi using a wide fan tip.

PROGUARD BUILDING • 14422 Best Ave • Santa Fe Springs, CA 90670 www.PROGUARDBUILDING.com • Phone 844-776-4273