

# SAFETY DATA SHEET 4000 Aqua Fast Base Coat

## **SECTION 1. IDENTIFICATION**

Product Name 4000 Aqua Fast Base Coat

Chemical Family Water-based Acrylic Coating

Recommended Use/Restrictions Coating for Roofing

Manufacturer Applications

**Proguard Building** 

14422 Best Ave., Santa Fe

Springs, CA 90670

24-Hour Emergency Phone 800.424.9300

Information Only 844.776.4273

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **GHS Classification**

Eye irritation: Category 2A
Skin sensitization: Category 1
Carcinogenicity: Category 1A

**GHS Label Elements** 

**!**>

Hazard pictograms:

Signal word: Danger

Hazard statements: May cause an allergic skin reaction.

Causes serious eye irritation.

May cause cancer.

Precautionary statements: **Prevention:** 

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood

Avoid breathing dust, mist, gas, vapors or spray. Wash skin and face thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace Wear permeation resistant protective gloves and clothing. Wear eye

and face protection.

Response:

IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap

and water. If skin irritation or rash occurs: Get medical attention. Wash

contaminated clothing before reuse.

Material Name: 4000 Aquathast Base Coat Page 1 of 10	SDS Version 1.1
--	-----------------

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage:

Store locked up.

Disposal:

Dispose of contents and container in accordance with existing federal, state, and local environmental control laws.

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 24 %

#### **SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS**

## **Hazardous Components**

Weight Percent	Components	CAS-No.	Classification
10 - 20%	Aluminum hydroxide	21645-51-2	Eye irritation Category 2B.
5 - 10%	Titanium dioxide (Rutile)	13463-67-7	Carcinogenicity Category 2 Inhalation. Specific target organ toxicity – single exposure Category 3 Respiratory system.
0.1 - 1%	Biocide	Trade Secret	Acute toxicity Category 2 Inhalation. Serious eye damage Category 1. Skin sensitization Category 1. Carcinogenicity Category 2.
0.1 - 1%	Ammonium Hydroxide	1336-21-6	Acute toxicity Category 4 Oral. Acute toxicity Category 3 Inhalation. Skin corrosion Category 1A. Serious eye damage Category 1.
0.1 - 1%	Crystalline Quartz Silica	14808-60-7	Acute toxicity Category 4 Oral. Carcinogenicity Category 1A. Specific target organ toxicity - repeated exposure Category 1 Lungs.

The specific chemical identity and/or exact percentage of component(s) have been withheld as a trade secret.

## **SECTION 4. FIRST AID MEASURES**

#### Most Important Symptom(s)/Effect(s)

**Acute:** Causes serious eye irritation with symptoms of reddening, tearing, swelling, and burning., May cause allergic skin reaction with symptoms of reddening, itching, swelling, and rash.

#### **Eve Contact**

In case of contact, flush eyes with plenty of lukewarm water. Get medical attention if irritation develops.

## **Skin Contact**

In case of skin contact, wash affected areas with soap and water. Immediately remove contaminated clothing and shoes. Get medical attention if irritation develops and persists.

## Inhalation

If inhaled, remove to fresh air. Get medical attention if irritation develops.

#### Ingestion

If ingested, do not induce vomiting unless directed to do so by medical personnel. Get medical attention.

Material Name: 4000 Aqua Fast Base Coat	Page <b>2</b> of <b>10</b>	SDS Version 1.1
---	----------------------------	-----------------

#### **SECTION 5. FIREFIGHTING MEASURES**

**Suitable Extinguishing Media:** All extinguishing media are suitable.

Unsuitable Extinguishing Media No Data Available

#### **Fire Fighting Procedure**

Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes. Use cold water spray to cool fire-exposed containers to minimize the risk of rupture.

## **Hazardous Decomposition Products**

By Thermal Decomposition: carbon monoxide, carbon dioxide, Acrylic monomers, other potentially toxic fumes

## **Unusual Fire/Explosion Hazards**

Toxic and irritating gases/fumes may be given off during burning or thermal decomposition.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

## **Spill and Leak Procedures**

Cleanup personnel must use appropriate personal protective equipment. Cover spill with inert material (e. g., dry sand or earth) and collect for proper disposal.

#### **SECTION 7. HANDLING AND STORAGE**

## **Handling/Storage Precautions**

Avoid breathing dust, vapor, or mist. Avoid contact with skin or clothing. Avoid contact with eyes. Use only with adequate ventilation/personal protection. Wash thoroughly after handling. Keep container closed when not in use. Protect from freezing.

#### **Storage Period:**

12 Months

**Storage Temperature** 

Minimum: 1 °C (33.8 °F) Maximum: 49 °C (120.2 °F)

## **Storage Conditions**

None known

#### **Substances to Avoid**

None known

#### **SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

## Aluminum hydroxide (21645-51-2)

US. ACGIH Threshold Limit Values

Time Weighted Average (TWA): 1 mg/m3 (Respirable fraction.)

US. ACGIH Threshold Limit Values

Hazard Designation: Group A4 Not classifiable as a human carcinogen.

Material Name: 4000 Aqua Fast Base Coat	Page <b>3</b> of <b>10</b>	SDS Version 1.1
---	----------------------------	-----------------

## Titanium dioxide (Rutile) (13463-67-7)

US. ACGIH Threshold Limit Values

Time Weighted Average (TWA): 10 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Permissible exposure limit: 15 mg/m3 (Total dust.)

US. ACGIH Threshold Limit Values

Hazard Designation: Group A4 Not classifiable as a human carcinogen.

#### Ammonium Hydroxide (1336-21-6)

US. ACGIH Threshold Limit Values

Time Weighted Average (TWA): 25 ppm

US. ACGIH Threshold Limit Values

Short Term Exposure Limit (STEL): 35 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Permissible exposure limit: 50 ppm, 35 mg/m3

## Crystalline Quartz Silica (14808-60-7)

US. ACGIH Threshold Limit Values

Time Weighted Average (TWA): 0.025 mg/m3 (Respirable fraction.)

US. OSHA Table Z-3 (29 CFR 1910.1000)

Time Weighted Average (TWA): 2.4 millions of particles per cubic foot of air (Respirable). The exposure limit is calculated from the equation, 250/(%SiO2+5), using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Time Weighted Average (TWA): 0.1 mg/m3 (Respirable). The exposure limit is calculated from the equation, 10/(%SiO2+2), using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Time Weighted Average (TWA): 0.3 mg/m3 (Total dust). The exposure limit is calculated from the equation, 30/(%SiO2+2), using a value of 100% SiO2. Lower values of % SiO2 will give higher exposure limits.

US. ACGIH Threshold Limit Values

Hazard Designation: Group A2 Suspected human carcinogen.

Any component which is listed in section 3 and is not listed in this section does not have a known ACGIH TLV, OSHA PEL or supplier recommended occupational exposure limit.

#### **Industrial Hygiene/Ventilation Measures**

General dilution and local exhaust as necessary to control airborne vapors, mists, dusts and thermal decomposition products below appropriate airborne concentration standards/guidelines.

## **Respiratory Protection**

In case of insufficient ventilation, wear suitable respiratory equipment.

#### **Hand Protection**

Permeation resistant gloves.

#### **Eye Protection**

Splash proof goggles.

Material Name: 4000 Aqua Fast Base Coat	Page <b>4</b> of <b>10</b>	SDS Version 1.1
---	----------------------------	-----------------

#### **Skin Protection**

Wear cloth work clothing including long pants and long-sleeved shirts.

#### **Additional Protective Measures**

Employees should wash their hands and face before eating, drinking, or using tobacco products. Educate and train employees in the safe use and handling of this product. Emergency showers and eye wash stations should be available.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

State of Matter:liquidColor:VariousOdor:Mild, AmineOdor Threshold:No Data AvailablepH:No Data Available

Freezing Point: 0 °C (32 °F) similar to water Boiling Point: 100 °C (212 °F) similar to water

Flash Point: Not applicable (water based product), however, solid material will

support combustion if water has been evaporated.

Evaporation Rate:No Data AvailableLower Explosion Limit:No Data AvailableUpper Explosion Limit:No Data Available

Vapor Pressure: 17 mmHg @ 20 °C (68 °F) similar to water

Vapor Density:No Data AvailableDensity:No Data AvailableRelative Vapor Density:No Data Available

Specific Gravity: 1.2 – 1.5

Solubility in Water:

Partition Coefficient: n-octanol/water:

Auto-ignition Temperature:

Decomposition Temperature:

Dynamic Viscosity:

No Data Available

#### **SECTION 10. STABILITY AND REACTIVITY**

#### **Hazardous Reactions**

Hazardous polymerization does not occur.

## Stability

Stable

#### **Materials to Avoid**

None known.

#### **Hazardous Decomposition Products**

By Thermal Decomposition: carbon monoxide, carbon dioxide, Acrylic monomers, other potentially toxic fumes

Material Name: 4000 Aqua Fast Base Coat	Page <b>5</b> of <b>10</b>	SDS Version 1.1
---	----------------------------	-----------------

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

Likely Routes of Exposure: Skin Contact

Eye Contact Ingestion Inhalation

## **Health Effects and Symptoms**

**Acute:** Causes serious eye irritation with symptoms of reddening, tearing, swelling, and burning., May cause allergic skin reaction with symptoms of reddening, itching, swelling, and rash.

Chronic: May cause cancer.

## **Toxicity Data for AF FOUNDATION**

No data available for this product.

## **Toxicity Data for Aluminum hydroxide**

#### **Acute Oral Toxicity**

LD50: > 2000 mg/kg (rat, female) (OECD Test Guideline 423)

#### Skin Irritation

rabbit, OECD Test Guideline 404, Non-irritating

#### Eye Irritation

rabbit, OECD Test Guideline 405, Slightly irritating

#### Sensitization

Respiratory sensitization: negative (mouse)

Studies of a comparable product.

Skin sensitization according to Magnusson/Kligmann (maximizing test): negative (guinea pig, OECD Test Guideline 406)

## **Repeated Dose Toxicity**

28 Days, Oral: NOAEL: 14,470 ppm, (rat, male)

## Mutagenicity

Genetic Toxicity in Vitro:

Mammalian cell - gene mutation assay: negative (Mouse lymphoma cells (L5178Y/TK), Metabolic Activation: with/without)

Genetic Toxicity in Vivo:

Micronucleus Assay: negative (rat, male/female, Oral) negative

## **Developmental Toxicity/Teratogenicity**

rat, female, oral, NOAEL (teratogenicity): 1,000 mg/kg, No Teratogenic effects observed at doses tested. No fetotoxicity observed at doses tested. rat, female, oral, GD 6-15, daily, NOAEL (teratogenicity): 266 mg/kg, No Teratogenic effects observed at doses tested.

No fetotoxicity observed at doses tested.

## **Toxicity Data for Titanium dioxide (Rutile)**

## **Acute Oral Toxicity**

LD50: > 5000 mg/kg (rat, female) (OECD Test Guideline 425)

Material Name: 4000 Aqua Fast Base Coat	Page <b>6</b> of <b>10</b>	SDS Version 1.1
---	----------------------------	-----------------

#### **Acute Inhalation Toxicity**

LC50: > 6.82 mg/l, 4 h (rat, male)

#### **Acute Dermal Toxicity**

LD50: > 10000 mg/kg (rabbit)

#### **Skin Irritation**

rabbit, OECD Test Guideline 404, Exposure Time: 24 h, Non-irritating

## **Eye Irritation**

rabbit, OECD Test Guideline 405, Non-irritating

#### Sensitization

dermal: non-sensitizer (Guinea pig, Maximization Test)

dermal: non-sensitizer (Human, Patch Test)

Skin sensitization (local lymph node assay (LLNA)):: negative (mouse, OECD Test Guideline 429)

## **Repeated Dose Toxicity**

28 Days, inhalation: NOAEL: 35 mg/m3, (Rat)

29 days, Oral: NOAEL: 24,000 mg/kg, (rat, male, daily)

up to 2 years, inhalation: NOAEL: 0.01 mg/l, (Rat, male/female, 6 hrs/day 5 days/week)

#### Mutagenicity

Genetic Toxicity in Vitro:

Ames: negative (Salmonella typhimurium, Metabolic Activation: with/without)

Mammalian cell - gene mutation assay: negative (Mouse lymphoma cells (L5178Y/TK), Metabolic Activation:

with/without)

Chromosome aberration test: negative (Chinese hamster ovary (CHO) cells, Metabolic Activation: with/without)

#### Genetic Toxicity in Vivo:

Drosophila SLRL test: negative (Drosophila melanogaster) negative

Cytogenetic assay: negative (mouse, male, intraperitoneal) negative

#### Carcinogenicity

Rat, Male/Female, inhalation, according to IARC, several rat inhalation and intratracheal installation studies using titanium dioxide have shown increases in benign and malignant lung tumors. Reviewed human exposure data did not suggest an association between occupational exposure to titanium dioxide and risk for cancer. Additionally, the IARC working group determined that, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other material, such as in paints."

## **Other Relevant Toxicity Information**

May cause irritation of respiratory tract.

#### <u>Toxicity Data for 1,3-Benzenedicarbonitrile, 2,4,5,6-tetrachloro-</u> Acute Oral Toxicity

LD50: > 10000 mg/kg (rat)

#### **Acute Inhalation Toxicity**

LC50: 0.217 mg/l, 4 h (rat) (OECD Test Guideline 403)

#### **Acute Dermal Toxicity**

LD50: > 10000 mg/kg (rabbit)

Material Name: 4000 Aqua Fast Base Coat	Page <b>7</b> of <b>10</b>	SDS Version 1.1
---	----------------------------	-----------------

#### Skin Irritation

rabbit, Draize, Non-irritating

## Eye Irritation severe

irritant

#### Sensitization

Skin sensitization: sensitizer (Human)

#### **Toxicity Data for Ammonium Hydroxide**

## Acute Oral Toxicity LD50: 350 mg/kg (rat)

## **Acute Inhalation Toxicity**

LC50: 2.87 mg/l, 4 h (rat)

#### **Skin Irritation**

Corrosive

## **Eye Irritation**

Human, Severely irritating

#### Sensitization

Skin sensitization: negative

#### Mutagenicity

Genetic Toxicity in Vitro:

Ames: negative (E. coli, Metabolic Activation: without)

## **Toxicity Data for Crystalline Quartz Silica**

## **Acute Oral Toxicity**

LD50: 500 mg/kg (rat)

## Mutagenicity

Genetic Toxicity in Vitro:

Ames: Negative results were reported in various in vitro studies. (Salmonella typhimurium, Metabolic Activation: with/without)

Genetic Toxicity in Vivo:

Sister Chromatid Exchange: ambiguous (hamster) ambiguous

## Carcinogenicity

rat, Male/Female, inhalation, 2 years, 6 hrs/day 5 days/week, positive

## **Carcinogenicity:**

Titanium dioxide (Rutile) IARC - Overall evaluation: 2B Possibly carcinogenic to humans.

Overall evaluation:

1,3-Benzenedicarbonitrile, IARC -

2,4,5,6-tetrachloro-

Crystalline Quartz Silica NTP - Hazard Designation: Known to be Human Carcinogen.

IARC - Overall evaluation: 1 Carcinogenic to humans.

2B Possibly carcinogenic to humans.

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecological Data for Titanium dioxide (Rutile)**

**Acute and Prolonged Toxicity to Fish** 

LC0: > 1,000 mg/l (Golden orfe (Leuciscus idus), 48 h)

## **Acute Toxicity to Aquatic Invertebrates**

EC0: > 3 mg/l (Water flea (Daphnia magna))

#### **Toxicity to Microorganisms**

EC0: > 10,000 mg/l, (Pseudomonas fluorescens, 24 h)

#### **Ecological Data for Biocide**

**Acute and Prolonged Toxicity to Fish** 

LC50: 0.049 mg/l (Other fish)

LC50: 0.076 mg/l (Rainbow (Donaldson)Trout (Oncorhynchus mykiss), 96 h)

## **Acute Toxicity to Aquatic Invertebrates**

EC50: 0.2 mg/l (Water flea (Daphnia magna))

## **Ecological Data for Ammonium Hydroxide**

**Additional Ecotoxicological Remarks** 

No data available for this component.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

## **Waste Disposal Method**

Waste disposal should be in accordance with existing federal, state and local environmental control laws.

#### **Container Precautions**

Recondition or dispose of empty container in accordance with governmental regulations. Do not reuse empty container without proper cleaning.

#### **SECTION 14. TRANSPORT INFORMATION**

Non-Regulated

#### **SECTION 15. REGULATORY INFORMATION**

## **United States Federal Regulations**

US. Toxic Substances Control Act: Listed on the TSCA Inventory.

## US. EPA CERCLA Hazardous Substances (40 CFR 302) Components:

None

#### SARA Section 311/312 Hazard Categories:

Acute Health Hazard Chronic Health Hazard

## US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A) Components:

None

Material Name: 4000 Aqua Fast Base Coat	Page <b>9</b> of <b>10</b>	SDS Version 1.1
---	----------------------------	-----------------

## US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required Components:

1,3-Benzenedicarbonitrile, 2,4,5,6-tetrachloro-

## US. EPA Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents (40 CFR 261):

Under RCRA, it is the responsibility of the person who generates a solid waste, as defined in 40 CFR 261.2, to determine if that waste is a hazardous waste.

#### **State Right-To-Know Information**

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

## Massachusetts, New Jersey or Pennsylvania Right to Know Substance Lists:

Weight percent	<u>Components</u>	<u>CAS-No.</u>
>=1%	Water	7732-18-5
>=1%	Acrylic Polymer	
20 - 30%	Limestone	1317-65-3
10 - 20%	Aluminum hydroxide	21645-51-2
0.1 - 1%	Crystalline Quartz Silica	14808-60-7

## New Jersey Environmental Hazardous Substances List and/or New Jersey RTK Special Hazardous Substances Lists:

Weight percent	<u>Components</u>	<u>CAS-No.</u>
0.1 - 1%	Zinc Oxide	1314-13-2
0.1 - 1%	Ammonium Hydroxide	1336-21-6
0.1 - 1%	Crystalline Quartz Silica	14808-60-7

## Massachusetts Right to Know Extraordinarily Hazardous Substance List:

Weight percent	<u>Components</u>	<u>CAS-No.</u>
0.1 - 1%	Crystalline Quartz Silica	14808-60-7

#### California Prop. 65:

Warning! This product contains chemical(s) known to the State of California to be Carcinogenic. Developmental toxin. Female reproductive toxin. Male reproductive toxin.

Weight percent	<u>Components</u>	<u>CAS-No.</u>
5 5 - 10%	Titanium dioxide (Rutile)	13463-67-7
0.1 - 1%	Crystalline Quartz Silica	14808-60-7

Based on information provided by our suppliers, this product is considered "DRC Conflict Free" as defined by the SEC Conflict Minerals Final Rule (Release No. 34-67716; File No. S7-40-10; Date: 2012-08-22).

## **SECTION 16. OTHER INFORMATION**

The method of hazard communication for Proguard Building is comprised of Product Labels and Safety Data Sheets.

Contact: Product Safety Department

Telephone: 832.922.2926 Version Date: 06/30/2016

SDS Version: 1.1

This information is furnished without warranty, express or implied. This information is believed to be accurate to the best knowledge of Proguard Building. The information in this SDS relates only to the specific material designated herein. Proguard Building assumes no legal responsibility for use of or reliance upon the information in this SDS.

Material Name: 4000 Aqua Fast Base Coat	Page <b>10</b> of <b>10</b>	SDS Version 1.1
---	-----------------------------	-----------------