

# RF100

## Reinforcing Fabric for Use with Roof Coating and Air and Water Resistive Barrier Systems

### Product Description

RF100 Reinforcing Fabric is a 100% polyester spun-laced textile for roofing and air and water resistive barrier applications. It is a high-tensile, high-tear strength, dimensionally stable fabric with excellent elongation for long-term performance. It is easy to apply with exceptional conformability, immediate wet-out and easy positioning/repositioning in coatings or sealants.

### Key Features and Typical Benefits

- **Applicator Friendly** – Easy to work with and install. Can easily be positioned / repositioned in coating without damage occurring to itself or the substrate.
- **Conformability** – Easily conforms to regular and irregular transitions, including, but not limited to: rough openings, penetrations, curbs, inside / outside corners, flashing, and more.
- **Seamless Wet Out** – Provides a monolithic and continuous reinforced surface, which allows coating to easily flow through and saturate.
- **High Strength Reinforcement** – Provides additional tensile and tear strength to help meet project needs.

### Potential Applications

- **AWB** – Spans static gaps up to 1/2" (13mm). Can treat: rough openings, penetrations, inside / outside corners, flashing, transitions, changes in plane, and more.
- **Roofing** – Can reinforce seams and curbs on roofing surfaces, including: metal, single-ply and modified bitumen seams as well as skylights, vents, scuppers, HVAC, and more.

Note: RF100 is not suitable for bridging dynamic gaps and expansion joints. Consider UltraSpan™ UST2200 silicone sheeting for these purposes.

### Packaging

- **Roll Length** – RF100 is available in 100 foot (30.5 m) rolls: and standard widths are: 4" (102 mm), 6" (152 mm), and 12" (305 mm). Additional widths may be available upon request.

### Color

- Color – White

### Typical Physical Properties

Typical property values of RF100 as supplied and cured are set forth in the table below.

#### Typical Properties

Property	Value <sup>(1)</sup>	Test Method
Weight	1.1 lbs (.5kg)	ASTM D3776
Oz./Sq./Yard (Grams/Sq. Meter)	1.6 oz (54.2g)	ASTM D3776
Bulk	22 mils	
Dry Tensile- MD	25 lbs (11.3kg)	ASTM D1777
Dry Tensile- CD	18 lbs (8.2kg)	ASTM D1777
Elongation- MD	45%	ASTM D1682
Mullen Burst	35 psi	ASTM D3786
Service Temperature Range	-40°F to +300°F (-40°C to 149°C)	

(1) Typical properties are average data and are not to be used as or to develop specifications.

### Installation

Refer to current roof coating and air and water resistive barrier coating specifications, installation guidelines and details for application instructions.

### Technical Services

Additional technical information and literature may be available from Momentive Performance Materials (MPM). Laboratory facilities and application engineering are available upon request from MPM.

### **Limitations**

Customers must evaluate MPM products and make their own determination as to fitness of use in their particular applications.

### **Patent Status**

Nothing contained herein shall be construed to imply the non-existence of any relevant patents or to constitute the permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

### **Product Safety, Handling and Storage**

Customers considering the use of this product should review the latest Material Safety Data Sheet and label for product safety information, handling instructions, personal protective equipment if necessary, and any special storage conditions required. Material Safety Data Sheets are available at [www.siliconesforbuilding.com](http://www.siliconesforbuilding.com) or, upon request, from any MPM representative. Use of other materials in conjunction with MPM sealants products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

## Customer Service Centers

<b>Americas</b>	+1 800 295 2392 Toll free Email: commercial.services@momentive.com
<b>Latin Americas</b>	<b>Brazil</b> +55 11 4534 9650 Direct Number Email: contato@momentive.com  <b>Mexico</b> +52 55 2169 7670 Direct Number Email: commercial.services@momentive.com
<b>EMEIA - Europe, Middle East, Africa, and India</b>	<b>Europe</b> +39 05 1092 4300 Direct Number  <b>Middle East, Africa and India</b> + 91 44 7121 2207 Direct Number* *All Middle Eastern countries, Africa, India, Pakistan, Bangladesh, Sri Lanka Email: 4information.eu@momentive.com
<b>APAC - Asia Pacific</b>	<b>China</b> 800 820 0202 Toll free +86 21 3860 4892 Direct Number  <b>Japan</b> Sales: JP.Silicones@momentive.com  <b>Korea</b> +82 2 6201 4600 Direct Number  <b>South East Asia, Australia &amp; New Zealand</b> +60 3 9206 1543 Direct Number* *South East Asia countries (Malaysia, Singapore, Thailand, Indonesia, Vietnam, Philippines, Cambodia, Myanmar / other countries located in Pacific region).
<b>MyMomentive™ Order Management Site</b>	shop.mymomentive.com

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBE HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

Before purchasing or using any Momentive products, please visit [www.siliconeforbuilding.com/legaldisclaimer](http://www.siliconeforbuilding.com/legaldisclaimer) to view our full product and sales disclaimer.

The use of the "TM" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc., or its affiliated companies.

Copyright 2024 Momentive Performance Materials Inc. All rights reserved.

**siliconesforbuilding.com**



**Licensed  
Partner**