



# Safety Walk Pad 7000

## Technical Data Sheet

For Professional Use Only

## Pre-Cured Silicone Safety Walk Pad

### Recommended Uses

ProRoof, Pre-Cured, Silicone Walk Pads may be rolled onto wet silicone coating to fully adhere to the roof surface. This surface will then be used as a designated walk pad, designed for light foot traffic and safety.

### Description

- A high quality, fully cured silicone sheet, reinforced with fiberglass
- Designed to provide a long-lasting flexible membrane that will retain this flexibility even in the harshest climatic conditions
- Formulated utilizing high quality silicone and fiberglass to create a very heat resistant and puncture resistant membrane
- Fully compatible with "Alkoxy" based silicone coatings and accessories
- Can come in a variety of colors with minimum purchase quantities

### Colors

**Standard Colors:** SAFETY YELLOW, Custom Colors per Request and Quantity minimums

### Packing/Shipping Information

#### CONTAINER SIZES:

1 Roll - Each roll is 1 meter wide & 50 meters long (3.2ft by 164ft)

1 Pallet (20 rolls)

SHIPPING CLASS - 55

## Typical Properties

Property	Test Method	Results
Heat Resistance (consistent)	ASTA E-84	550 F
Heat Resistant (sparks)	ASTA E-84	1265 F
Tensile Strength	ASTM D-2370	1850 PSI
Permeance	ASTM D-1653	12 Perms
Elongation	ASTM D-2370	24.6%
Tear Resistance	ASTM D-624	440 PSI
Thickness		.9mm +/- .05
Weight		12oz / Square Foot
Reflectivity	ASTM C-1549	94%
Emittance	ASTM C-1371	92%
SRI	Calculated	99 (white only)

## Surface Preparation

**General:** Surfaces should be properly prepared with an Alkoxy silicone coating system. An additional layer of silicone should be applied to the area receiving the walk pad at a rate of 1 gallon per 100 square feet. While the coating is still wet, roll the pre-cured walkpad into the wet silicone. Allow to cure for 24 hours before allowing foot traffic on the walkpad. If there are installation questions, please contact Proguard Building representative before proceeding.

**Ponded Water:** Proguard warranties do not cover damage due to ponding water. The National Roofing Contractors Association considers ponding water on any roof unacceptable.

No warranty is expressed or implied regarding the wearability, waterproofing, slip resistance or other feature of this product.

## Applications

This product may be rolled over wet Alkoxy silicone to properly adhere. Allow 24 hours to cure before allowing foot traffic

**Coverage Rate:**

Apply 1 gallon per square foot of Alkoxy silicone in area intended to be covered by walkpad. Roll walkpad out while silicone is still wet.

## Safe Practices

The product is designed for professional installation. Before working with this product, you must read and become familiar with the available information on its risks, proper use and handling. Information sources include, but not limited to, SDS and product labels. More resources are available at [proguardbuilding.com](http://proguardbuilding.com) or by contacting Proguard Building directly.

---

**PROGUARD BUILDING - 14422 Best Ave - Santa Fe Springs, CA 90670**